



300 & 400 SERIES UNITS - STRUCTURE SPECIFICATIONS

<u>TYPE</u>	<u>PRC</u>	<u>STROKES</u>	<u>TYPE</u>	<u>PRC</u>	<u>STROKES</u>
300	4500	24"-18"	326	12000	42"-32"-22"
300B	6000	24"-18"	326	12000	45"-34.2"-23.6"
301	12000	45"-34.2"-23.6"	326	12000	48"-37.3"-26.7"
302	15000	44"-34"-24"	327	18500	44"-34"-24"
302	15000	54"-44"-34"-24"	327	18500	54"-44"-34"-24"
303	20000	54"-44"-34"-24"	352	12000	45"-34.2"-23.6"
304	25000	54"-44"-34"-24"	353	15000	44"-34"-24"
305	25000	74"-64"-54"-44"	353	15000	54"-44"-34"-24"
306D	9700	42"-32"-22"	354	20000	54"-44"-34"-24"
307	8000	34"-27"-20"	355	25000	54"-44"-34"-24"
308	8000	34"-27"-20"	356	25000	74"-64"-54"-34"
308B	8000	34"-27"-20"	401	12000	44.2"-33.6"-23.2"
308C	10000	22"-16.5"	402	15000	44"-34"-24"
309	8000	34"-27"-20"	402	15000	54"-44"-34"-24"
309	8000	34"-26"-18"	406	9700	42"-32"-22"
311	10000	42"-32"-22"			

500 SERIES REDUCERS - SPECIFICATIONS

<u>TYPE</u>	<u>HORSEPOWER</u>	<u>PEAK TORQUE (In-#)</u>	<u>RATIO</u>	<u>OIL CAP (Gal)</u>
500	2	9,900	28.8	
500A	3.5	17,300	27.2	4-1/2
501	7.4	36,600	27.7	11-1/2
503	10.5	52,000	30.2	16
504	15	74,000	30.0	17
505	22	109,000	30.6	29
506	35	173,000	29.4	29
507	45	223,000	30.1	30
511	8	39,600	27.7	12-1/2
513	12	59,400	30.2	16
551	27	135,000	10.0	34
552	32	158,000	10.0	34
553	40	198,000	9.06	33
554	48	238,000	9.4	41
555	71	350,000	9.0	55

STANDARD PUMPING UNIT COMBINATIONS

300	500A	308	501
301	504	309	501
302	} 505, 506 507, 551 552, 553 554, 555	352	504
303		353	} 505, 506 507, 551 552, 553 554, 555
304		354	
305		355	
306D	503	356	