

Lone Star ALS

Counterweight Dimensions

Counterweight No.	0	1	2	3	4	5	6	7	8	9	10
A	57.1	49.25	47.25	43.25	43.25	43.25	39.375	35.5	29.5	25.5	19.7
B	66.92	66.875	66.875	59.0625	59.0625	55.125	49.1875	45.25	39.375	31.5	21.7
C	8.66	9.5	7.875	8	7.25	6.75	6.75	5.875	5.875	5.875	5.1
D	23	18.5	17.75	16.75	16.75	16.75	15	14	11.5	10	8.3
E	13.78	11.875	11.875	11.875	10.5	8.875	8.875	6.875	6.875	6.875	6.9
F	19.68	19.75	19.75	17.75	17.75	15.75	15.75	15.75	13.75	14.625	11.8
G	23.62	23.625	23.625	23.625	23.625	23.625	19.625	19.625	15.75	9.625	6.7
H	27.56	23.625	23.625	23.625	23.625	23.625	19.625	19.625	7.875	9.125	8.7
I		5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.25	0.0
R	106.3	102.375	102.375	102.375	94.5	76.875	76.875	66.325	66.375	54	43.3
A - D	34.1	30.8	29.5	26.5	26.5	26.5	24.4	21.5	18.0	15.5	11.4
Weight/ea, lbs											
2H, (2 bolt holes)				3750	3395	2755	2200	1650	1215	750	346.0
3H, (3 bolt holes)	6400	5280	4211	3582	3247						

weights in lbs. & dimensions in inches

